



# PHYSICAL PROPERTIES AND THECNICAL INFORMATION

TRADE NAME

**T 150 EP**

COMPOSITION

**NBR -PVC**

CELLULAR STUCTURE

CLOSED CELL SPONGE RUBBER

COLOUR

BLACK

DENSITY (Kg/m³)

ISO 845-88

70 ± 15

COMPRESSION DEFLECTION

NF R 99-211 50% (kPa)

70

WATER ABSORPTION

ASTM D 1056-00

<5 %

LINEAR SHRINKAGE

22 h 70°C

% < 5%

ELONGATION AT BREAK

ISO 1798-97

≥ 90 %

TENSILE STRENGTH

ISO 1798-97

≥ 150 kPa

TEMPERATURE RANGE

STATIC

FROM - 40° C

CONSTANT

0° C / + 90° C

INTERMITTENT

MAX + 105° C

RESISTANCE

AIR + U.V.

GOOD

OZONE

GOOD

OIL

EXCELLENT

ACIDS

GOOD

FIRE ( NFP 92507 & NF F 16-101)

M1 F4

PEUGEOT -RENAULT M.E. 1333

TYPE A

FIRE ( FMVSS 302 & UL 94 HF1)

SELF ESTINGUISHING HF1

ENVIRONMENTAL PROTECTION

CFC & HCFC FREE

RECYCLING

CAN BE RECYCLED